



Martindale Abrasion: Greater than 1 million rubs

FR Properties AS1530.3: Smoke Developed Index = 5

Colourfastness to Light (ISO 105-B02): 6 - 7

Composition: 85% PVC 15% Polyester

SPECIFICATIONS

Pattern Repeat: Plain Railroaded: No

Width/Roll Length: 137cm/30m

Care Label: C

Warranty*: 3 Year Available Colours: 52

*Conditions Apply



Scan the QR Code with your device to view the Studio Encore range and order free sample cuttings.

COLOURWAYS













WEDGEWOOD

WINDSOR



SPECIFICATIONS

Application	Heavy Commercial, Healthcare, Hospitality & Marine Upholstery
Abrasion Resistance	Test method AS 2001.2.25 (12kPa) Martindale Method No significant wear after 1 Million+ Rubs
Anti Microbial & Anti Bacterial	Sanitised to inhibit growth of Mould and Bacteria
Composition	85% PVC 15% Polyester Gauge: 1.0mm Roll Length: 30m Roll Width: 137cm
Colour Fastness to Light	UV Stabilised and suitable for indoor/outdoor use. Light Fastness rating 6-7 ISO 105-B02-1994 (Grey Scale 1-5)
Colour Fastness to Bleach	Tested to Australian Standards (AS2001.4) No change of colour rating 4-5
Meets FR Standards for use in Commercial Areas:	FR Properties: Tested to Australian Standards (AS1530.3) Spread of Flame: 0 Smoke Developed: 5, IMO Standards A. 652(16) AS/NZS 3837
Reach Certification	Compliant with the EU Reach regulation (EC) No 1907/2006 The Reach Certification restricts the use of harmful chemicals that potentially have an impact on both human health & the environment. Studio Encore is Phthalate Free. No Formaldehyde, Lead, Mercury or Chromium used in the manufacturing process.
Protech	A protective top surface allowing easy removal of stains and dirt
Care & Cleaning	Most stains can be cleaned using warm soapy water, followed by clean water rinsing. Moderate scrubbing with a medium bristle brush will help loosen soiling from the embossed surface. Failure to follow cleaning instructions may permanently stain and reduce the life of the vinyl.

